

# INNER TUBE VALVE SPECIFICATIONS

# AIR LOG



## OFF CENTER VALVES



Valve #	Height	Stem Diameter	Application
<b>TR6</b>	1.16"	.29"	ATV / UTV and Lawn & Garden
<b>TR13</b>	1.38"	.46"	Lawn & Garden, Passenger and Light Truck
<b>TR15</b>	1.38"	.65"	Front Tractor, Implement and Industrial Construction
<b>TR150</b>	3.48"	.61"	Light Truck, Trailer, Front Tractor and Implement
<b>TR300</b>	2.05"	.61"	Truck, Bus, Trailer and Irrigation
<b>TR218A</b>	.94"	.64"	Tractor, Implement and Construction
<b>TR220A</b>	1.34"	.64"	OTR, Industrial and Construction

## ON CENTER VALVES



Valve #	Full Length	Before Bend	After Bend	Degree of Bend	Application
<b>JS2</b>	-	1.02"	1.31"	70°	Forklift, Small Industrial and Material Handling
<b>TR87</b>	-	.59"	1.31"	90°	
<b>TR244</b>	-	1.02"	1.31"	90°	
<b>TR75A (TR440)</b>	3.74"	.94"	2.99"	86°	Industrial, Forklift, Mining and Commercial Truck
<b>TR77A (TR442)</b>	4.88"	.94"	4.13"	86°	
<b>TR78A (TR444)</b>	5.75"	.94"	5.00"	86°	
<b>TR175A (TR443)</b>	5.28"	.94"	4.53"	86°	
<b>TR177A (TR441)</b>	4.49"	.94"	3.74"	86°	
<b>TR179A (TR445)</b>	6.30"	.94"	5.55"	86°	
<b>V3-06-6</b>	5.16"	.81" / 2.46"	1.93"	90° / 41°	Large Industrial and Mining
<b>J1175C</b>	4.02"	1.38"	4.13"	88°	Large Industrial, OTR and Mining